

5-6 Watts	10-12 Watts	12-18 Watts	18-24 Watts	30-36 Watts	40-60 Watts	60-90 Watts	120-240 Watts
<p>GT-83083-0505-USB 5 Watts Vout=5 49.2 x 47.0 x 27.5</p>	<p>GT-83084-10VV-USB 10 Watts Vout=5-5.2 51.5 x 23.5 x 38.5 ±0.3</p>	<p>GT-46120-12VV-X.X 12 Watts Vout=5-48 64.0 x 40.5 x 31.5</p>	<p>GTM96180-18VV 18 Watts Vout=4-48 74 x 43.5 x 36.8</p>	<p>GTM91120-30VV-FW 30 Watts Vout=5-48 102 x 46 x 37</p>	<p>GT-46401-40VV-X.X-Q 40 Watts Vout=12-48 90.0 x 38.0 x 59.4</p>	<p>GTM43007-BWVVV-F 60 Watts Vout=5-48 101.6 x 50.8 x 22.5</p>	<p>GTM961200P-120VV 120 Watts Vout=12-54 149.30" x 62.80 x 34.0</p>
<p>GTM96060-06VV-Q 6 Watts Vout=3.3-48 43.5 x 74.0 x 36.8</p>	<p>GT-86120-WWVV 10 Watts Vout=5, 12 70 x 32.8 x 48.5</p>	<p>GT-86120-WWVV-X.X-W2E 12 Watts Vout=5, 12 69 x 28.8 x 58.3</p>	<p>GTM41080-18VV-F 18 Watts Vout=5-48 74 x 44 x 34</p>	<p>GTM91120CC-30VV-P2 30 Watts Vout=5-48 102 x 46 x 37</p>	<p>GT-46400-40VV-X.X 40 Watts Vout=12-48 111 x 52 x 32.3</p>	<p>GTM91099-60VV-P3 60 Watts Vout=5-48</p>	<p>GTM43004P-WWVV-X.X-F 120 Watts Vout=5-48 184.0 X 62.0 X 37.5</p>
<p>GT-46060-06VV-X.X-Q 6 Watts Vout=5-24 40.5 x 64.0 x 30.0</p>	<p>GTM46101-10VV-X.X-USB 10 Watts Vout=5-5.5 41.0 x 71.0 x 31.5</p>	<p>GTM46161-16VV-X.X-USB 16 Watts Vout=5-5.5 41.0 x 71.0 x 31.5</p>	<p>GTM93021-20VV-P2 20 Watts Vout=5-48 51.0 x 48.0 x 35.0</p>	<p>GT-83082-3612-W2/W2E 36 Watts Vout=12 93 x 33 x 78.69 ±0.5</p>	<p>GTM96600-60VV 60 Watts Vout=5-54 117.5 x 53.5 x 34.2</p>	<p>GT-96600-7056-T3-AP 70 Watts Vout=56 165x32.5x56.5</p>	<p>GTM43004P-WWVV-X.X-P3 120 Watts Vout=5-48 178.0x76.0x39.5</p>
<p>GT-86060-06VV-X.X-W2 6 Watts Vout=5, 12 66.5 x 25.5 x 51.3</p>	<p>GT-86120-WWVV-X.X-W2C 12 Watts Vout=5, 12 69 x 28.8 x 40.3</p>	<p>GT-96180-1856-R2-AP 18 Watts Vout=56</p>	<p>GT-46240-24VV 24 Watts Vout=12-24 80.6 x 50.0 x 31.0</p>	<p>GTM96300-36VV-R2/R3A 36 Watts Vout=5-48 74 x 43.5 x 36.8</p>	<p>GTM96600-60VV-R 60 Watts Vout=5-48 117.53 x 53.47 x 36.6</p>	<p>GTM96700-BWVVV-F 70 Watts Vout=5-48 101.6 x 50.8 x 30.5</p>	<p>GTM961600P-180VV 180 Watts Vout=12-54 173 x 72 x 38</p>
<p>GTM41134-WWVV-F 6 Watts Vout=3.3-48 84.5 x 41.5 x 17.0</p>	<p>GT-86120-WWVV-X.X-W2 12 Watts Vout=5, 12 69 x 28.8 x 40.3</p>	<p>GTM96180-18VV 18 Watts Vout=5-48 74x43.5x36.8</p>	<p>GT-86240-WWVV-X.X 24 Watts Vout=12 73.5 x 35 x 57</p>	<p>GT-96300-3656-AP 36 Watts Vout=56 107 x 55 x 36</p>	<p>GTM43007-AWWVVV-F 60 Watts Vout=5-48 76.2 x 50.8 x 23.6 with heat sink 76.2 x 50.8 x 22.5 without heat sink</p>	<p>GTM96900P90VV-X.X 90 Watts Vout=12-54 149.38 x 62.6 x 33.5 ±1.0</p>	<p>GTM91110P240XX 240 Watts VOUT=12-55 127 x 76 x 43</p>

Battery Packs

BL0105F2635161S1PCAT

Lithium Polymer
3.7VDC, 105mAh
Battery Pack
Dimensions:
2.8 x 16.5 x 37
Configuration: 1S 1P
Cell Type: ICR18650-26F
Cell Shape: Cylindrical
IEC 62133 Certified



BL1880F6835661S5PX9M

Lithium Polymer
3.7VDC, 9400mAh
Battery Pack
Dimensions:
185.5 x 69.5 x 7.9 mm
10K NTC Thermistor
BQ27200
Configuration: 1S 5P
Cell Type: GP683566
Cell Shape: Rectangular
IEC 62133 Certified



BL0750F5030481S1PCMC

Lithium Polymer
3.7VDC, 700mAh
Battery Pack
Dimensions:
50.5 x 30.5 x 5.3
10K NTC Thermistor
Configuration: 1S 1P
Cell Type: GP503048
Cell Shape: Rectangular
IEC 62133 Certified
UL 2054 Certified




Custom Battery Packs

Contact GlobTek with your specifications



BL1200P4054481S1PCAC

Lithium Polymer
3.7VDC, 1200mAh
Battery Pack
Dimensions:
53.0 x 48.0 x 4
10K NTC Thermistor
Configuration: 1S 1P
Cell Type: GP404852
Cell Shape: Rectangular
IEC 62133 Certified



BL2600C18654S1PXX

Lithium Ion
14.8VDC, 2600mAh
Battery Pack Dimensions: 77 x 69
Fuel Gauge
Configuration: 4S 1P
Cell Type: ICR18650-26F
Cell Shape: Cylindrical
IEC 62133 Certified



BL2200F6034501S2XXXX

Lithium Ion
3.7VDC, 2200mAh
Battery Pack
Dimensions: 51 x 34 x 13
Configuration: 1S 2P
Cell Type: 603450
Cell Shape: Rectangular
IEC 62133 Certified



BL2600C1865004S1PG1

Lithium Ion
14.8VDC, 2600mAh
Battery Pack
Dimensions:
66 x 73.5 x 28.5
Fuel Gauge/Built In
Charger Circuitry
4S 1P
Cell Type: ICR18650-26F
Cell Shape: Cylindrical
IEC 62133 Certified



BL2600C1865001S2PXXXX

Lithium Ion
3.7VDC, 5200mAh
Battery Pack
Dimensions:
19 x 68.5 x 37
Configuration: 1S 2P
Cell Type: ICR18650-26F
Cell Shape: Cylindrical
IEC 62133 Certified



GTM91128

Smart Battery Charger
Available in versions delivering 4.2V, 8.4V, or 12.6V at 1A to address single or multiple battery configurations



International Power Cords

Type 451

North America
NEMA 1-15P
10A, 13A/125V~



Type 302

North America
NEMA 5-15P
10A, 13A/15A/125V~



Type 119

North America
NEMA 5-15P Hospital Grade
10A, 13A/15A/125V~



Type 703

IEC 60320-C7
2.5A/250V~



Type 701

IEC 60320-C13
10A, 13A, 15A
125V~, 250V



Type 712

IEC 60320-C5
2.5A, 10A/250V~



Type 7033

IEC 60320-C19
12A, 14A, 16A
125~250V



Type 705

IEC 60320-C14
10A, 13A, 15A/250V~



Type PZ0800

United Kingdom
BS1363
13A/250V~



Type 207

"Europlug"
CEE7 Standard XVI
(CEE 7/16)
2.5A/250V



Type 2314

Schuko Europe
CEE7 Standard sh 7
16A/250V



Type 550

Australia, New Zealand
AS/NZS 3112
10A/250V~



Type 205

India IS 1293
6A/250V~



Type 208

South Africa SABS 164-1
16A/250V~



Type 219

Argentina IRAM 2073
10A/250V~



Type 204B

Brazil NBR 14136
10A/250V~



Type 602

China GB 1002
10A/250V~



Type 377C

Israel
16A/250V~



Type 2302

Italy CEI 23-16
10A/250V~



Type 2313K

Korea KS C 8305
16A/250V~

